

Technical Data Sheet

StoDivers UR

Maintenance cleaning agent for floor coatings
already treated with floor care products



Characteristics

- Area of application**
- Interior and exposed to weathering
 - As a maintenance cleaner on Sto floor coating systems treated with StoDivers P 105 / 110 / 120

- Properties**
- Due to a neutral formulation, streak-free cleaning is possible without affecting the gloss
 - The low-foaming adjustment means it can be used in all floor scrubber dryers
 - Water-based

Technical Data

Criteria	Standard / test specification	Value / Unit	Notes
Density	EN ISO 2811	1.0 g/cm ³	
pH Value		8.5	

The characteristic values stated are average values or approximate values. Due to the natural raw materials in our products, the stated values can vary slightly in the same delivery batch; this does not affect the suitability of the product for its intended use.

Substrate

- Requirements** The substrate must be free from loose and coarse dirt.

Application

- Application temperature** Lowest application temperature: +8°C
Highest application temperature: +30°C

- Time for application** Depends on the degree of soiling

- Coating build-up** StoDivers UR maintenance cleaner

- Application**
- With a mop or floor scrubber dryer
Maintenance cleaning with StoDivers UR
- Manual cleaning:
Dilute StoDivers UR with approx. 10 : 100 parts by weight of cold water in a pail.
Then clean the floor using a clean mop. Collect the loosened dirt.
- Cleaning by machine:
Depending on the degree of soiling, dilute StoDivers UR with 10 : 50 to 10 : 100 parts by weight of cold water.
Go over the surface with the floor scrubber dryer and suction up the waste water at the same time.
For stubborn soiling, first leave the cleaning solution to react for approx. 5 minutes, then scrub or suction clean the floor.

Technical Data Sheet

StoDivers UR

Cleaning the tools	Clean with water.
Notes, recommendations, special information, miscellaneous	Please consult the local sales office for further information and any site assistance required.

Delivery

Packaging	Name	Container
	StoDivers UR	5 lit

Storage

Storage conditions	Store in cool dry conditions; avoid direct sunlight.
Storage life	This product has a shelf life of 48 months from the manufacturing date.

Identification

Product group	Supplementary & Maintenance Products
----------------------	--------------------------------------

Safety	Please refer to Safety Data Sheet.
---------------	------------------------------------

Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on www.sto-sea.com.

Sto SEA Pte Ltd
159 Sin Ming Road
#06-02 Amtech Building
Singapore 575625
Phone: +65 6453 3080
Fax : +65 6453 3543
info.sg@sto.com
www.sto-sea.com

Sto SEA Sdn Bhd
28, Jalan Rajawali 3
Bandar Puchong Jaya,
47170 Selangor, Malaysia
Phone: +60 3 8080 9066
Fax: +60 3 8080 9255
info.sg@sto.com
www.sto-sea.com

Sto SEA Pte Ltd
3656/49-52 Green Tower, 16th Floor
Rama IV Rd, Klongton, Klongtoei,
10110 Bangkok, Thailand
Phone: +66 2 1684 921 Ext. 230
Fax: +66 2 1684 999
info.sg@sto.com
www.sto-sea.com

StoCretec GmbH
Gutenbergstr. 6
65830 Kriftel,
Germany
Phone: +49 6192 401 104
Fax: +49 6192 401 105
info.sg@sto.com
www.sto-sea.com

*Product images may differ from the actual product.